












120 W UNIVERSAL AC ADAPTOR CONNECTOR SPECIFICATION

NO.	PICTURE	OUTPUT VOLTAGE	RANGE VOLTAGE	OUTPUT CURRENT (MAX)	CONNECTOR SPEC.	FOR LAPTOP MOULD
A		19V	18.2-19.5V	6.3A	Φ4.8*1.7*10.7MM DC-F	HP/COMPAQ: 18.5V/2.7A, 18.5V/3.5A, 18.5V/3.8A, 18.5V/4.5A, 18.5V/4.9A, 18.5V/6.5A, 19V/6.3A, 19V/6.5A DELTA: 19V/2.64A, 19V/6.3A; ASUS: 19V/2.64A; NEC: 19V/2.64, ETC.
B		15V	14.2-15.5V	8A	Φ6.3*3.0*10.7MM	TOSHIBA: 15V/3A, 15V/4A, 15V/5A, 15V/6A, 15V/8A; NEC: 15V/6A, ETC.
C		19V	18.2-19.5V	6.3A	Φ5.5*2.1*10.7MM DC-F	ACER: 19V/3.16A, 19V/3.42A, 19V/4.74A; LITEON: 19V/3.16A, 19V/3.42A; NEC: 19V/3.16A, ETC.
D		19V	18.2-19.5V	6.3A	Φ5.5*2.5*12MM DC-F	IBM: 19V/4.2A; DELL: 19V/3.16A, 19V/3.42A, 19V/6.3A; COMPAQ/HP: 18.5V/4.9A, 19V/4.9A; DELTA: 18.5V/6.5A, 19V/2.64A, 19V/6.3A, 19V/6.5A; TOSHIBA: 19V/3.16A, 19V/3.42A, 19V/4.7A, 19V/6.3A; LITEON: 19V/3.16A,

F		19V	18.2-19.5V	6.3A	Φ5.5*3.0*10.7MM PIN1.0	SAMSUNG: 19V/3.16A, 19V/3.75A, 19V/4.22A, 19V/4.74A, ETC
G		16V	15.2-16.5V	7.5A	Φ6.0*4.3*10.7MM PIN1.0	SONY: 16V/3.42A, 16V/3.75A, 16V/4A; FUJITSU: 16V/3.36A, 16V/3.75A, ETC
H		19.5V	19.2-20.5V	6.15A	Φ6.0*4.3*10.7MM PIN1.0	SONY: 19.5V/2.7A, 19.5V/3A, 19.5V/4.1A, 19.5V/4.7A, 19.5V/5.13A, 19.5V/6.15A; FUJITSU: 19V/3.16A, 19V/3.69A, 19V/4.22A, ETC
I		19V	18.2-19.5V	6.3A	Φ5.5*1.7*10.7MM DC-F	TOSHIBA: 19V/3.95A; ACER: 19V/3.42A; DELTA: 20V/3.5A, ETC.

J		19.5V	18.7-20.0V	6.15A	Φ7.4*5.0*12.5MM PIN0.6	DELL: 19.5V/3.34A, 19.5V/4.62A, ETC.
K		20V	19.2-20.5V	6A	W7.3*7.4MM 3 PIN	DELL: 20V/3.5A, 20V/4.5A, ETC.
P		15V	14.2-15.5V	8A	W9.2*6.4MM 4 PIN	TOSHIBA: 15V/8A, ETC.

No. A, B, D, J, P are included in the package and the others are optional.
Please contact with your vendor for more information.